



Zebra® GT800™ Desktop Printer



SEE MORE. DO MORE.



Compact design with affordability, versatility and ease of use

Providing great performance and reliability at a competitive price, the GT800 direct-thermal/thermal-transfer desktop printer offers a wide range of advanced features to meet a variety of low-to-medium volume printing applications.

The GT800 printer supports both 74-metre and 300-metre ribbon capacities and, because its intelligent design means that no additional settings are required for supporting different roll lengths, it is easy for users to select the appropriate length for the task in hand.

Larger ribbon capacity (requiring less frequent replacement) and its simplicity of use combine with reliability and compact design to make this printer an ideal choice for commercial environments with moderate printing requirements.

With a full feature set and competitive pricing, the GT800 desktop printer provides an affordable route to Zebra quality.

Intuitive and durable design

The intuitive design of the GT800 printer combines with a choice of three connectivity interfaces and optional 10/100 Ethernet, co-resident EPL2™ and ZPL II® programming languages, Unicode™ and optional ZBI 2.0™ to ensure that integration is quick and efficient.

Print speeds of up to 127mm per second, a powerful processor and memory allocation make label processing and throughput fast and easy whilst ongoing management of the product and operator intervention are kept to a minimum with status reporting, odometer control and increased ribbon capacity.

A durable, compact design supporting a range of media with widths of up to 114mm, the GT800 printer is an excellent choice for customers looking to migrate easily or upgrade from a competitor's thermal-transfer desktop printer.

Ideal for these applications:

- **Healthcare**
 - Document archiving
 - Specimen labelling
 - Sterile services labelling
 - Thermal transfer patient identification
- **Manufacturing**
 - Agency labels
 - Product labelling
- **Retail**
 - Outdoor product labelling
 - Retail pharmacy labelling and safety labels
 - Speciality printing
- **Security**
 - Asset marking
 - Evidence tracking
- **Supply chain**
 - Product and shipping labels for outdoor use

SPECIFICATIONS AT A GLANCE*

ZEBRA GT800 DESKTOP PRINTER

Printer name	Ribbon characteristics	Firmware
• GT800	Outside diameter <ul style="list-style-type: none">• 66mm/2.6" (300m roll); 34mm/1.34" (74m roll)	<ul style="list-style-type: none">• ZPL II: Zebra Programming Language provides sophisticated label formatting and printer control and is compatible with tabletop and mobile Zebra printers
Standard features <ul style="list-style-type: none">• 300- or 74-metre ribbon handling• 32-bit RISC processor• Co-resident EPL2 and ZPL II programming languages• Triple connectivity: serial, USB and parallel• Print methods: thermal-transfer and direct-thermal modes; printing of barcodes, text and graphics• OpenACCESS™ for easy media and ribbon loading• Microsoft® Windows® drivers• Odometer• Unicode™• ENERGY STAR®-compliant• Intelligent clutch – no switching or additional setup required• No secondary cores on genuine Zebra ribbon	Standard length <ul style="list-style-type: none">• 300m (984'); 74m (242')	<ul style="list-style-type: none">• EPL2: Eltron Programming Language with Line Mode simplifies label formatting and enables format compatibility with legacy applications
	Ratio <ul style="list-style-type: none">• 1:4 (one 300m roll of ribbon per four rolls of media)• 1:1 (one 74m roll of ribbon per roll of media)	<ul style="list-style-type: none">• ZBI 2.0: a powerful programming language that lets printers run standalone applications, connect to peripherals and much more
	Width <ul style="list-style-type: none">• 33.8mm/1.33" to 110mm/4.3"	<ul style="list-style-type: none">• XML-enabled printing
	Core internal diameter <ul style="list-style-type: none">• 300m ribbon: 25.4mm/1.00"• 74m ribbon: 12.7mm/0.5"	Networking/Connectivity <ul style="list-style-type: none">• Ethernet: internal 10/100 offered in combination with USB and serial interface (replaces parallel port)
Printer specifications	Operating characteristics	Fonts/Graphics/Symbologies
Resolution <ul style="list-style-type: none">• 203dpi/8 dots per mm	Environment <ul style="list-style-type: none">• Operating temp.: 5°C/40°F to 41°C/105°F• Storage temp.: -40°C/-40°F to 60°C/140°F• Operating humidity: 10% to 90% non-condensing R.H.• Storage humidity: 5% to 95% non-condensing R.H.	<ul style="list-style-type: none">• Unicode-compliant for multi-language applications• 16 resident expandable ZPL fonts• One resident scalable ZPL font• Five resident expandable EPL2 fonts• Supports user-defined fonts and graphics, including custom logos
Memory <ul style="list-style-type: none">Standard: 8MB flash, 8MB SDRAM	Agency approvals <ul style="list-style-type: none">• TÜV-R NRTL, TÜV-R CB, NOM, KCC, CE, FCC Class B	Barcode symbologies <ul style="list-style-type: none">• Barcode ratios: 2:1 (non-rotated) and 3:1 linear barcodes: Codabar, Code 11 (ZPL), Code 39, Code 93, Code 128, EAN-8, EAN-13, EAN-14 (ZPL), German Post Code (EPL), GS1 DataBar (formerly RSS), Industrial 2-of-5 (ZPL), Interleaved 2-of-5, ISBT-128 (ZPL), Japanese Postnet (EPL), Logmars (ZPL), MSI, Plessey, Postnet, Standard 2-of-5 (ZPL), UCC/EAN-128 (EPL), UPC-A, UPC and EAN 2 or 5 digit extensions (ZPL), UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E• Two-dimensional barcodes: Aztec Code, Codablock (ZPL), Code 49 (ZPL), Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code• For EPL and ZPL except where noted
Print width <ul style="list-style-type: none">• 104mm/4.09"	Physical characteristics <ul style="list-style-type: none">• Width: 197mm/7.75"• Height: 184mm/7.25"• Depth: 273mm/10.75"• Weight: 5kg/10.98lb	Communication and interface capabilities <ul style="list-style-type: none">• Centronics® parallel (36-pin) connector ports• Auto-sensing RS-232 serial interface• ZebraNet 10/100 Print Server (optional)
Print length <ul style="list-style-type: none">• 991mm/39"	ZebraLink™ Solutions <ul style="list-style-type: none">Software<ul style="list-style-type: none">• ZebraDesigner™ Pro: an intuitive, easy-to-use software program for creating complex label designs (option)• ZebraDesigner: offers basic features for simple label design• ZebraNet™ Bridge Enterprise: centrally manage Zebra printers from a single PC screen anywhere on your global network (unlicensed product free, licensed product option)• ZebraNet Utilities v7.0: provides enhanced printing, conversion and administration capabilities; message management; and more• ZebraDesigner Driver: the most powerful driver available from Zebra• Web View: connect and control Zebra barcode printers via the printer's Web interface using a common Web browser and ZPL™• Alert: printers equipped with ZebraNet print servers will notify you via any email-enabled wired or wireless device to minimise downtime• POS driver	Options and accessories <ul style="list-style-type: none">• Dispenser – label peel and present with label-present sensor• ZebraNet 10/100 Print Server – internal and external Ethernet options for network communication and printing• KDU and KDU Plus™ – keyboard display units for standalone printing applications
Print speed <ul style="list-style-type: none">• 203dpi: 127mm/5" per second		Electrical specifications <ul style="list-style-type: none">• Auto-ranging external power supply with C5-type connector• Output: 20VDC, 2.5A• Input: 100–240VAC, 50–60Hz
Media sensors <ul style="list-style-type: none">• Fixed reflective and transmissive sensors		
Media characteristics		
Media width <ul style="list-style-type: none">• 19.5mm/0.75" to 114mm/4.49"		
Media length <ul style="list-style-type: none">• 6.5mm/0.25" to 991mm/39"		
Maximum media roll size <ul style="list-style-type: none">• 127mm/5" O.D. on a 25.4mm/1.00" or 38mm/1.5" I.D. core		
Media thickness <ul style="list-style-type: none">• 0.08mm/0.003" to 0.19mm/0.007"		
Media types <ul style="list-style-type: none">• Roll-fed or fan-fold• Label stock (die-cut or continuous, direct-thermal or thermal-transfer)• Tag stock (die-cut or continuous, direct-thermal or thermal-transfer)		



OPTIMAL
MOBILE COMPUTING AND SOFTWARE

OPTIM-AL LTD

Bulgaria, 1612 Sofia, 7 Tzar Boris III, Blvd.

+359 /2 951 67 22, info@optim-al.com, www.optim-al.com

*Specifications subject to change without notice.

©2013 ZIH Corp. EPL2, KDU Plus, OpenACCESS, ZebraDesigner, ZebraLink, ZebraNet, ZBI 2.0, ZPL and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Unicode is a trademark of Unicode, Inc. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ENERGY STAR is a registered trademark of the Environmental Protection Agency. Centronics is a registered trademark of Centronics Data Computer Corporation. All other trademarks are the property of their respective owners.